



PRODUCT INFORMATION

oilfino Duo Extreme



DESCRIPTION

oilfino Duo Extreme is a fully synthetic 2-stroke engine oil that has been specially developed for high loads in karting, road and off-road racing. It is intended for use in heavy-duty engines with air or water cooling, premixed or in oil injection systems with oil/gasoline mixtures depending on the mixing ratio as specified by the manufacturers.

PROPERTIES

The low ash and 100% synthetic formulation with excellent temperature stability prevents the formation of deposits and thus also misfires and premature ignitions caused by deposits. Other advantages: Prevents jamming of moving parts and blockage of the exhaust system. It has excellent lubrication and wear protection of bearings and cylinders, excellent rust and corrosion protection, very good temperature behaviour; self-mixing in oil injection systems or premixing.

SPECIFICATIONS

- API TC
- ISO-L-EGD

RECOMMENDATION

- JASO FD
- TISI

Specific data	Method	Unit	oilfino Duo Extreme
Density at 15°C	D 1298	kg/m ³	894
Kin. viscosity at 40 °C	D 445	mm ² /s	56.8
Kin. viscosity at 100 °C	D 445	mm ² /s	9.1
Viscosity index	D 2270		137
Sulphate ash	D 874	% mass	0.18
Flash point	D 93	°C	115
Pour point	D 97	°C	-45

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.