



oilfino Cultor M 15W-40



DESCRIPTION

oilfino Cultor M 15W-40 is a modern multi-purpose oil that has been specially developed for agricultural machinery, excavators and construction machinery. It is made from carefully selected, solvent-refined base oils. By adding specially developed additives on a synthetic basis, this special oil has the following properties: It has a high dispersing and detergent capacity, which means that it effectively removes dirt and deposits. It offers comprehensive protection against wear, corrosion and foaming. In addition, it is very resistant to oxidation and has excellent high-pressure properties. The high and stable viscosity index ensures that the oil retains its lubricating properties even under extreme conditions. The oilfino Cultor M 15W-40 is thus a reliable and powerful oil for use in agricultural and construction machinery.

PROPERTIES

oilfino Cultor M 15W-40 is a multi-purpose oil for agricultural machinery, excavators and construction machinery. It is made from carefully selected, solvent-refined base oils and contains specially developed synthetic-based additives. These additives give the oil a number of outstanding properties, including a high dispersing and detergent capacity, comprehensive protection against wear, corrosion and foaming, high oxidation resistance, excellent high-pressure properties and a high and stable viscosity index. The oilfino Cultor M 15W-40 is thus a powerful and reliable oil that meets the requirements of agricultural and construction machinery.

SPECIFICATIONS

- ACEA E3
- API GL-4
- API GL-5 (Low speed/high torque)
- API CG-4
- API SF/CE

RECOMMENDATION

- CASE MAT 3525
- NH NH 024C
- FORD ESN
- CASE MAT 3526
- ZF TE-ML 06A
- M2C159 B/C
- JD J27
- ZF TE-ML 03A
- FORD FNH 82009203
- JD J20C
- ZF TE-ML 06B
- Sauer Sunstrand/Danfoss Hydro Static Trans Fluid
- MF M 1135
- ZF TE-ML 07B
- ALLISON C4 (Agriculture applic.)
- MF M 1139
- ZF TE-ML 05K
- EATON VICKERS M-2950-S
- MF M 1143
- ZF TE-ML 06C
- DIN 51524 T3 HVLDP
- MF M 1144
- ZF TE-ML 07D
- MF M 1145
- FORD ESN-M2C134 C/D

Specific data	Method	Unit	oilfino Cultor M 15W-40
Density at 15°C	ASTM D4052	g/ml	0.876
Dynamic viscosity at -20°C	ASTM D5293	mPa.s	5600
Viscosity at 40 °C	ASTM D445	mm ² /s	103,00
Viscosity at 100 °C	ASTM D445	mm ² /s	14.30
Viscosity index	ASTM D2270		142
Flash point COC	ASTM D92	°C	222
Flow point	DIN ISO 3016	°C	-36
Base number	ASTM D2896	mg KOH/g	10.7

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.