



oilfino Cultor UTTO



DESCRIPTION

oilfino Cultor Utto is a universal transmission/hydraulic oil for supplying farm tractors, agricultural machinery and construction machinery with a common oil circuit for transmission/axle drive and hydraulics.

PROPERTIES

The oilfino Cultor UTTO ensures immediate response of hydraulic systems at low outside temperatures and high lubrication resistance in power transmission under extreme stresses. It prevents the slipping of IPTO clutches and the coefficient of friction has been adjusted to the special requirements of the wet brakes running in the oil bath. The regulations of well-known tractor manufacturers are exceeded, and oilfino Cultor Utto can easily be used with the specifications listed below.

SPECIFICATIONS

- API GL-4

RECOMMENDATION

- John Deere J20C/J20D
- Ford M2C86A/B
- Ford M2C134D
- Allison C-4
- Caterpillar TO-2
- Case MS 1204/6/7/9
- MF M1135/1143/1145
- NH410B
- NH420A
- CNH MAT 3525/3526
- Oliver: Type 55/Type 5J
- New Holland 82948718
- I.H.C: B-5 & B-6 Hydran
- Volvo WB101 (97303)
- Valtra G2-08 / G2-B10
- White: Q-1705/1722/1766B
- White: Q-1802/1826
- ZF TE-ML 03E/05F/06K

Specific data	Method	Unit	oilfino Cultor UTTO
SAE grade	DIN 51511		70W-85 / 10W-30
Density at 15°C	ASTM D 1298	kg/m ³	887
Viscosity at 40 °C	ASTM D 445	mm ² /s	52
Viscosity at 100 °C	ASTM D 445	mm ² /s	10.4
Viscosity index	ASTM D 2270		154
Flash point	DIN ISO 2592	°C	225
Pour point	DIN ISO 3016	°C	-39

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.