



oilfino Performance Multi 5W-30



DESCRIPTION

oilfino Performance Multi 5W-30 is an ultra-high-performance long-life engine oil for the latest passenger car engines based on state-of-the-art synthesis technology and a coordinated innovative additive. Excellent cold start behaviour ensures optimum lubrication reliability in the cold running phase. Extreme loads and high temperatures are reliably controlled under all operating conditions. It ensures very high wear protection, significantly reduced friction losses and is extremely shear-resistant. Due to the highest requirements for fuel savings, oilfino Performance Multi 5W-30 contributes to the protection of the environment by reducing emissions (CO₂ reduction). Minimum evaporation tendency reduces oil consumption and enables the longest oil change intervals according to the respective manufacturer's instructions. By using oilfino Performance Multi 5W-30, premature fuel ignition LSPI (Low Speed Pre-Ignition) and associated engine damage are avoided.

PROPERTIES

oilfino Performance Multi 5W-30 is suitable for use in the latest engines such as diesel engines with EURO 6 (DPF) and SCR exhaust gas aftertreatment, as well as gasoline engines with exhaust gas turbocharging and GPF. It has been developed for VW engines with maintenance interval extension (WIV), among other things, and is therefore suitable for oil change intervals of up to two years. oilfino Performance Multi 5W-30 can be used in almost all long-life VW engines and is backwards compatible. The corresponding operating material regulations must be observed.

SPECIFICATIONS

- ACEA C2
- ACEA C3
- API SN Plus
- API SP

RECOMMENDATION

- BMW Longlife-04
- MB 229.51
- MB 229.52
- MB 229.31
- Porsche C30
- VW 50400/50700
- VW 50301
- FIAT 9.55535 S3
- OPEL OV 0401547 D30
- OPEL OV 0401547 G30

RELEASES

- BMW Longlife-04
- VW 50400/50700
- MB 229.52

| Specific data | Method | Unit | oilfino Performance Multi 5W30 |
|-------------------------|-----------------|--------------------|--------------------------------|
| SAE grade | SAE J 300 | | 5W-30 |
| Density at 15°C | DIN 51 757 | kg/cm ³ | 851 |
| Kin. viscosity at 40°C | DIN EN ISO 3104 | mm ² /s | 67.6 |
| Kin. viscosity at 100°C | DIN EN ISO 3104 | mm ² /s | 11.8 |
| Flash point COC | DIN EN ISO 2592 | °C | 233 |
| Pour point | DIN EN ISO 3016 | °C | -42 |

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.