



PRODUCT INFORMATION

oilfino Via Eco Plus 5W-40



DESCRIPTION

oilfino Via Eco Plus 5W-40 is a universal multi-range engine oil based on synthesis technology. It offers a variety of excellent properties such as stable viscosity, good shear stability, excellent cold start properties, safe lubrication layer at high temperatures, reduced ash formation, detergent and dispersant properties as well as protection against wear, corrosion and foaming.

PROPERTIES

This smooth-running engine oil is suitable for modern gasoline and diesel engines, also with turbochargers in passenger cars and transporters.

SPECIFICATIONS

- API SN/CF
- ACEA C3

RECOMMENDATION

- VW 505 01
- VW 505 00
- BMW LONGLIFE-04
- GM dexos2™
- PORSCHE A40
- MB 226.5
- MB 229.31
- MB 229.51
- RENAULT RN 0700
- RENAULT RN 0710
- FORD WSS-M2C917-A
- FIAT 9.55535-S2
- FIAT 9.55535-GH2

Specific data	Method	Unit	oilfino Via Eco Plus 5W-40
Density at 15 °C		kg/l	0.850
Viscosity 40 °C		mm ² /s	75.80
Viscosity 100 °C		mm ² /s	13.20
Viscosity index			180
Flash point COC		°C	220
Flow point		°C	-36
Base number		mgKOH/g	7.0
Sulphate ashgehalt		%	0.75

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.