



PRODUCT INFORMATION

oilfino Via Eco V 0W-30



DESCRIPTION

A universal easy spin multi-range engine oil, developed according to the latest technical progress, based on synthesis technology and special synthetic base oils. Carefully chosen, highly effective additives give this excellent high performance motor oil the following features: Fuel-saving in partial and full-load operation, suitable for modern catalytic converters, reduced ash formation (mid SAPS), very good cold start properties, a safe lubricating film at high operating temperatures, extended oil change intervals, very good detergent and dispersing properties, excellent protection against wear, corrosion and foaming.

PROPERTIES

A fuel-saving, specially compiled engine oil, which is excellently suitable for modern gasoline and diesel engines in passenger cars, with and without turbochargers in passenger cars and transporters, with extended oil exchange intervals. Moreover, this oil prolongs the life of the particle filter. Due to its special composition, this product is ideally suited for use for VW 504.00/507.00 requirements, the so-called VW Longlife III.

SPECIFICATIONS

- ACEA C3
- ACEA C2
- API SN

RECOMMENDATION

- PORSCHE C30
- VW 504 00/507 00
- VW TL 52545
- MB 229.31
- MB 229.51
- BMW LONGLIFE-04
- FIAT 9.55535-DS1
- FIAT 9.55535-GS1
- FIAT 9.55535-S3

RELEASES

- VW 504 00/507 00
- MB 229.51
- BMW LONGLIFE-04

Specific data	Method	Unit	oilfino Via Eco V 0W-30
Density at 15 °C	ASTM D4052	g/ml	0.842
Viscosity 40 °C	ASTM D445	mm ² /s	59.0
Viscosity 100 °C	ASTM D445	mm ² /s	11.7
Viscosity index	ASTM D2270		197
Stockpunkt	ASTM D6892	°C	-48
Base number	ASTM D2896	mgKOH/g	8.3
Colour			brown

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.