



PRODUCT INFORMATION

oilfino Via Extra 5W-40



DESCRIPTION

oilfino Via Extra is a synthetic high-performance smooth-running engine oil for petrol and diesel engines with and without turbocharging. State-of-the-art synthesis technology in conjunction with an extremely low cold viscosity and stable high-temperature viscosity ensures a significant fuel saving potential.

PROPERTIES

oilfino Via Extra ensures wear protection and excellent oxidation stability through the selected combination of high-quality synthetic components and selected additives. The balanced additive ensures very good engine cleanliness and prevents the formation of black sludge.

SPECIFICATIONS

- ACEA A3/B4-16
- API SN/CF

RECOMMENDATION

- VW 505 00
- VW 502 00
- BMW LONGLIFE-01
- PSA B71 2296
- PORSCHE A40
- MB 226.5
- MB 229.3
- MB 229.5
- RENAULT RN 0700
- RENAULT RN 0710
- OPEL GM-LL-B-025
- FIAT 9.55535-M2
- FIAT 9.55535-Z2
- FIAT 9.55535-H2
- FIAT 9.55535-N2
- CHRYSLER MS 12991

RELEASES

- MB 229.3

Specific data	Method	Unit	oilfino Via Extra 5W-40
SAE grade	SAE J 300		5W-40
Density at 15°C	DIN 51757	Kg/m ³	856
Viscosity at 40 °C	DIN 51562	mm ² /s	85.3
Viscosity at 100 °C	DIN 51562	mm ² /s	14.1
Viscosity index	DIN ISO 2909		171
Flash point	DIN ISO 2592	°C	236
Pour point	DIN ISO 3016	°C	-42
Base number	DIN ISO 3771	mgKOH/g	11.3
Sulphate ash	DIN 51575	g/100g	1.2

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.