



oilfino Via Rallye 15W-40



DESCRIPTION

oilfino Via Rallye is a mineral oil-based high-performance universal engine oil for diesel and petrol engines with or without turbocharging. It ensures reliable cold starts all year round and shear-stable active ingredients ensure high-temperature resistance over the full oil residence time. oilfino Via Rallye was developed for the universal supply of mixed fleets.

PROPERTIES

oilfino Via Rallye ensures wear protection through the selected combination of high-quality base oils and selected additives, and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevent the formation of black sludge.

SPECIFICATIONS

- ACEA A3/B4
- E7
- API SL/CI-4
- JASO DH-1
- GLOBAL DHD-1

RECOMMENDATION

- DTFR 15B110 (MB 228.3)
- Cummins CES 20078
- Deutz DQC III-18
- MB 229.1H
- Volvo VDS-3 (STD 417-0002)
- Caterpillar ECF-2
- Renault VI RLD / RLD-2
- MAN M 3275-1
- Mack EO-N
- Detroit Diesel DDC 93K215
- MTU MTL 5044 Type 2

Specific data	Method	Unit	oilfino Via Rallye 15W-40
SAE grade	SAE J 300		15W-40
Density at 15°C	DIN 51 757	g/cm ³	0.883
Viscosity at 40 °C	DIN EN ISO 3104	mm ² /s	104
Viscosity at 100 °C	DIN EN ISO 3104	mm ² /s	14.0
Viscosity index	DIN ISO 2909		136
Flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	-39
Base number	ASTM D 2896	mgKOH/g	11.0

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.