



PRODUCT INFORMATION

# oilfino Via Top 10W-40



## DESCRIPTION

Oilfino Via Top is a semi-synthetic high-performance engine oil for petrol and diesel engines with and without turbocharging. By using synthetic components, friction losses in the engine are reduced and fuel savings and lower environmental impact are achieved.

## PROPERTIES

oilfino Via Top ensures wear protection through the selected combination of high-quality base oils and selected additives, and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevent the formation of black sludge. Deposits, sludge and lacquering are prevented by low evaporation losses and ensure clean pistons and piston ring grooves.

## SPECIFICATIONS

- ACEA A3/B4
- ACEA A3/B3-16
- API SN/CF

## RECOMMENDATION

- MB 229.1
- VW 501 01
- VW 505 00
- FIAT 9.55535-D2
- FIAT 9.55535-G2
- RENAULT RN 0700
- RENAULT RN 0710

Specific data	Method	Unit	oilfino Via Top 10W-40
SAE grade	DIN 51511		10W-40
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	873
Viscosity at 40 °C	DIN 51562	mm <sup>2</sup> /s	94.6
Viscosity at 100 °C	DIN 51562	mm <sup>2</sup> /s	14.0
Viscosity index	DIN ISO 2909		155
Flash point	DIN ISO 2592	°C	232
Pour point	DIN ISO 3016	°C	-28
Base number	DIN ISO 3771	mgKOH/g	7.9
Sulphate ash	DIN 51575	g/100g	0.95

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.