



oilfino Via Ultra LL 5W-30



DESCRIPTION

oilfino Via Ultra LL is a synthetic high-performance long-life engine oil for modern passenger car engines of the latest generation. Specially designed to save fuel with normal and extended oil change intervals (up to 50,000 km or two years).

PROPERTIES

oilfino Via Ultra LL maintains the exhaust systems of diesel engines for a very long time due to its low-pollution composition and the low sulphur and phosphorus content reduces pollution of catalytic converters in gasoline engines. Due to its low evaporation rate and high fuel savings, oilfino Via Ultra LL 5W-30 reduces emissions and protects the environment. Very good pumpability, even at low temperatures, ensures optimum lubrication reliability in the cold running phase. The excellent HTHS viscosity (High Temperature High Share) ensures safe operation of the engine even under extreme loads and high temperatures.

SPECIFICATIONS

- ACEA C3
- API SN
- ACEA C2
- API CF

RECOMMENDATION

- BMW LONGLIFE-04
- MB 229.51
- MB 229.52
- PORSCHE C30
- VW 504 00/507 00
- Please observe prescribed oil change intervals.
- Not usable for the following Volkswagen pump/nozzle diesel engines: R5, V10 TDI with and without DPF before 2006.

For these engine generations, the VW standard 506.01 SAE 0W-30 is to be used.

Specific data	Method	Unit	oilfino Via ultra LL 5W-30
SAE grade	DIN 51511		5W-30
Density at 15°C	ASTM D4052	g/ml	0.856
Viscosity at -30 °C	DIN 51377	mPAs	5950
Viscosity at 40 °C	ASTM D445	mm ² /s	68.0
Viscosity at 100 °C	ASTM D445	mm ² /s	11.7
Viscosity index	ASTM D2270		169
Flash point	ASTM D92	°C	230
Pour point	ASTM D6892	°C	-39
Sulphate ash	ASTM D874	Mass %	0.7

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.