



oilfino Via Ultra Pro 5W-30



DESCRIPTION

oilfino Via Ultra Pro 5W-30 is a synthetic high-performance smooth-running engine oil for modern passenger car engines of the latest generation. State-of-the-art synthesis technology in conjunction with an extremely low cold viscosity and stable high-temperature viscosity ensures a significant fuel saving potential. The synthetic base oils used with matched innovative additive technology with reduced sulphate ash weight ensure compliance with current practical requirements and maintain the effectiveness of the exhaust gas purification systems. Specially developed for vehicles with diesel particulate filters that use an engine oil according to ACEA C1 or ACEA C2 or require engine oils according to ACEA A1/B1 or A5/B5.

PROPERTIES

oilfino Via Ultra Pro 5W-30 maintains the exhaust systems of diesel engines for a very long time due to its low-pollution composition and the low sulphur and phosphorus content reduces pollution of catalytic converters in gasoline engines. Due to its low evaporation rate and high fuel savings, oilfino Via Ultra Pro 5W-30 reduces emissions and protects the environment. Very good pumpability, even at low temperatures, ensures optimum lubrication reliability in the cold running phase. The excellent HTHS viscosity (High Temperature High Share) ensures safe operation of the engine even under extreme loads and high temperatures.

SPECIFICATIONS

- API SN/CF
- ACEA C2

RECOMMENDATION

- RENAULT RN 0700
- FIAT 9.55535-S1
- PSA B71 2290-2014

Specific data	Method	Unit	oilfino Via Ultra Pro 5W-30
SAE grade	DIN 51511		5W-30
Density at 15°C	DIN 51757	kg/m ³	849
Viscosity at -30 °C	DIN 51377	mPAs	4200
Viscosity at 40 °C	DIN 51562	mm ² /s	51.8
Viscosity at 100 °C	DIN 51562	mm ² /s	9.7
Viscosity index	DIN ISO 2909		177
Flash point	DIN ISO 2592	°C	235
Pour point	DIN ISO 3016	°C	-40
Base number	DIN ISO 3771	mgKOH/g	6.4
Sulphate ash	DIN 51575	g/100g	0.49

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.