



DESCRIPTION

oilfino CVT-Fluid is a synthetic high-performance transmission oil specially designed for use in modern continuously variable automotive transmissions.

PROPERTIES

In addition to a high level of wear protection, the synthetic base of the oilfino CVT-Fluid in combination with state-of-the-art additive technology ensures optimised power transmission – both with a CVT chain and with a CVT thrust link belt. The neutral behaviour towards sealing materials prevents the formation of leaks and thus combines long service intervals with a long service life of the transmission. Due to the high shear strength and extremely low foaming tendency, the transmission is protected from wear and makes oilfino CVT-Fluid a high-quality lubricant in the field of continuously variable automotive transmissions.

RECOMMENDATION

- Audi Multitronic
- BMW Mini Cooper EZL799
- Daihatsu Ammix CVT DFE
- Daihatsu Ammix CVT Fluid DC
- Daihatsu Ammix CVT Fluid DFC
- Dodge / Jeep / Chrysler NS-2
- Dodge / Chrysler / Jeep Mopar CVT+4
- GM / Saturn DEX-CVT
- Honda HMMF (without starting clutch)
- Honda HCF2
- Honda Z-1 (CVT model)
- without starting clutch
- not SFU for 2001 – 2007 Honda Fit & Jazz)
- Hyundai / KIA SP III (CVT model)
- Idemitsu CVTS-EX1
- Mazda JWS 3320
- MB 236.20
- Mitsubishi Diaqueen CVTF-J1
- Mitsubishi Diaqueen CVTF-J4 and J4+
- Mitsubishi Diaqueen SP-III (CVT model only)
- Nissan NS-1/ NS-2/ NS-3
- Punch CVT
- Shell Green 1V
- Subaru iCVT
- Subaru iCVT FG
- Subaru ECVT
- Subaru Lineartronic chain CVT and CVT II Fluid
- Subaru Lineartronic High Torque (HT) CVT Fluid
- Suzuki CVTF TC
- Suzuki CVTF 3320
- Suzuki NS-2
- Suzuki CVT Green 1&2
- Toyota CVTF TC
- Toyota CVTF FE
- VW TL 521 16 (G 052 516)
- VW TL 521 80 (G 052 180)

Specific data	Method	Unit	oilfino CVT-Fluid
Appearance			blank & clear
Density at 15°C	DIN 51757	Kg/m ³	848
Kinematic viscosity at 40°C	DIN 51562	mm ² /s	7.3
Kinematic viscosity at 100°C	DIN 51562	mm ² /s	35.2
Viscosity index	DIN ISO 2909		178
Flash point	DIN ISO 2592	°C	214
Pour point	DIN ISO 3016	°C	-48
Base number	DIN ISO 3771	mg/KOH/g	3.7

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.