



oilfino Varius DSG-Fluid 75W



DESCRIPTION

oilfino Varius DSG-Fluid is a highly developed, complex special transmission oil that meets the high requirements for use in dual-clutch transmissions in particular.

PROPERTIES

The properties of oilfino Varius DSG Fluid have been tailored to the requirements of the sports sector. It always ensures the same stable friction characteristic under the toughest thermal loads both in winter operation and in summer heat. Thanks to its excellent additive combination, oilfino Varius DSG Fluid offers excellent wear, corrosion and ageing protection in addition to exceptionally high shear stability.

RECOMMENDATION

- BMW DCTF-1/ DCTF-1+/ DCTF-2
- BMW Drivelogic 7-speed (Getrag)
- BMW 6-speed DCT
- BMW MTF LT-5
- Borg Warner
- Bugatti Veyron
- Chrysler 68044345 EA & GA
- Chrysler Powershift 6-speed (Getrag)
- Ferrari 7-speed (Getrag)
- Ferrari TF DCT-3
- Fiat 9.55550-MZ6
- Ford / Nissan Powershift 6-speed (GFT)
- Ford WSS-M2C 936 A
- Ford WSS-M2C 200-D2/XT-11-QDC
- Ford WSS-M2C 218-A1/ Ford F-DC
- Mitsubishi TC-SST 6-speed (GFT)
- Mitsubishi MZ320065 DiaQueen SSTF-1
- Peugeot / Citroen DCS 6-speed (GFT)
- PSA 9734 S2
- Porsche 999.917.080.01
- Renault EDC 6-speed (Getrag)/ EDC-7
- Renault 77 11 785 243 (DWS)
- Volvo Powershift 6-speed (GFT)
- Volvo 1161838/ 1161839
- VW G 052 536/ 055 536
- VW (Audi/ Seat/ Skoda) 6-speed
- VW/Audi TL 52 182 / G 052 182 A2 or A6 (fluid)
- VW/ TL 52 529 / G 052 529 A2 or A6 (fluid) / DSG7 = S-Tronic 7
- VW (Audi/ Seat/ Skoda) 7-speed
- VW/Audi G 055 529
- VW/Audi G 055 512
- ZF / Porsche Oil #999.917.080.00
- VW Golf GTE DQ400E

Specific data	Method	Unit	oilfino Varius DSG-Fluid
SAE grade	SAE J 306		75W
Appearance	DIN 10964		blank & clear
Density at 15°C	DIN EN ISO 12185	Kg/m ³	854
Kinematic viscosity at 40°C	DIN EN ISO 3104	mm ² /s	7.3
Kinematic viscosity at 100°C	DIN EN ISO 3104	mm ² /s	34.3
Viscosity index	DIN ISO 2909		173
Dynamic viscosity at -40°C	ASTM D2983	mPa*s	12,100
Flash point	DIN EN ISO 2592	°C	201
Pour point	DIN ISO 3016	°C	-51
Evaporation loss 1h 200°C	DIN 51581-1	Mass %	2
Tapered roller bearing shear test, loss (20h)	CEC-L-45-A-99	%	8.2
Tapered roller bearing shear test, viscosity after lubrication (20h)	CEC-L-45-A-99	mm ² /s	6.76
FZG test A/8.3/90 // A/16.6/90	DIN ISO 14635		>12 // > 12

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.