



oilfino Varius G 400 LS 85W-90



DESCRIPTION

Hypoid transmission oils for drive axles with self-locking differential. Contains special additives to limit slip (limited slip) and prevents noise formation under the highest mechanical and thermal loads.

PROPERTIES

The selected base oils with matching additive technology guarantee very good afterflow behaviour at low temperatures and high lubrication safety at high operating temperatures. Lubrication safety is guaranteed even under the highest mechanical continuous and impact loads due to the excellent wear protection.

SPECIFICATIONS

- API GL-5

RECOMMENDATION

- ZF TE-ML 05C (ZF003494)
- ZF TE-ML 12C (ZF003494)
- ZF TE-ML 21C (ZF003494)
- ZF TE-ML 07A
- ZF TE-ML 08
- ZF TE-ML 16E
- Ford M2C 104 A

RELEASES

- ZF TE-ML 05C (ZF003494)
- ZF TE-ML 12C (ZF003494)
- ZF TE-ML 21C (ZF003494)
- ZF TE-ML 16E
- Ford M2C 104 A

Specific data	Method	Unit	oilfino Varius G 400 LS
SAE grade	DIN 51512		85W-90
Density at 15°C	ASTM D 1298	kg/m ³	899
Kinematic viscosity at 40 °C	ASTM D 445	mm ² /s	154
Kinematic viscosity at 100 °C	ASTM D 445	mm ² /s	16.2
Viscosity index	ASTM D 2270		108
minimaler Phosphorwert		ppm	2350
Pour point	ASTM D 97	°C	-30

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.