



PRODUCT INFORMATION

oilfino Varius G 500 80W-90



DESCRIPTION

oilfino Varius G 500 are high-quality hypoid transmission oils for highly stressed hypoid-toothed drive axles of PASSENGER CARS and commercial vehicles.

PROPERTIES

oilfino Varius G 500 offers excellent wear protection and excellent oxidation and temperature stability even under extreme operation and the toughest conditions. The selected base oils with matching additive technology guarantee very good afterflow behaviour at low temperatures and high lubrication safety at high operating temperatures.

SPECIFICATIONS

- API GL-5

RECOMMENDATION

- MIL PRF – 2105 D
- MAN 342 Typ M2
- ZF ZF001911 ZF TE-ML 05A/ 12E/ 16B/ 17B/ 19B/ 21A

RELEASES

- ZF ZF001911 ZF TE-ML 16B/ 17B/ 19B/ 21A (SAE 80W-90 only)

Specific data	Method	Unit	oilfino Varius G 500
SAE grade	SAE J 306		80W-90
Density at 15°C	DIN 51757	kg/m ³	892
Kinematic viscosity at 40 °C	DIN 51398	mm ² /s	140
Kinematic viscosity at 100 °C	DIN 51398	mm ² /s	14.1
Viscosity index	D 2270		98
Flash point	DIN ISO 2592	°C	230
Pour point	DIN ISO 3016	°C	-33
FZG test A/8.3/90	DIN ISO 14635		>12

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.