



PRODUCT INFORMATION

oilfino Varius G 500 90



DESCRIPTION

oilfino Varius G 500 are high-quality hypoid transmission oils for highly stressed hypoid-toothed drive axles of PASSENGER CARS and commercial vehicles.

PROPERTIES

oilfino Varius G 500 offers excellent wear protection and excellent oxidation and temperature stability even under extreme operation and the toughest conditions. The selected base oils with matching additive technology guarantee very good afterflow behaviour at low temperatures and high lubrication safety at high operating temperatures.

SPECIFICATIONS

- API GL5

RECOMMENDATION

- MILL2105 C/D
- MAN 342 M1
- Voith 3.325339
- MB 235.0
- ZF TEML 16B/16C/16D/17B/19B/21A
- DAF
- Ford SQM2C9002 AA
- Volvo 97310
- Renault

Specific data	Method	Unit	oilfino Varius G 500		
SAE grade	SAE J 306		80W-90	90	85W-140
Density at 15°C	DIN 51757	kg/m ³	892	902	906
Kinematic viscosity at 40 °C	DIN 51398	mm ² /s	140	198	337
Kinematic viscosity at 100 °C	DIN 51398	mm ² /s	14.1	17.6	24.2
Viscosity index	D 2270		98	95	96
Flash point	DIN ISO 2592	°C	230	216	220
Pour point	DIN ISO 3016	°C	-33	-24	-21
FZG test A/8.3/90	DIN ISO 14635		>12	>12	>12

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.