



# oilfino Varius G 550 80W-90



## DESCRIPTION

**oilfino Varius G 550** are high-quality hypoid transmission oils for highly stressed hypoid-toothed drive axles of passenger cars and commercial vehicles.

## PROPERTIES

oilfino Varius G 550 offers excellent wear protection and excellent oxidation and temperature stability even under extreme operation and the toughest conditions. The selected base oils with matching additive technology guarantee very good afterflow behaviour at low temperatures and high lubrication safety at high operating temperatures.

## SPECIFICATIONS

- API GL-4
- API GL-5
- API MT-1

## RECOMMENDATION

- SAE J 2360 (MIL-PRF-2105 D/E)
- MB release 235.0
- MB release DTFR 12B100
- MAN 341 type Z2
- MAN 341 GA1
- MAN 342 type M2
- Scania STO 1:0
- Scania STO 1:1 G
- ZF release number ZF000447 ZF TE-ML 02B/ 05A/12L/12M/16B/17H/ 19B/ 21A
- Robert Bosch TE ML 08
- Ford M2C197-A
- Mack GO-J
- ZF TE-ML 07A
- Arvin Meritor Transmission O-94
- Volvo 97321
- DAF
- IVECO

Specific data	Method	Unit	oilfino Varius G 550
SAE grade	SAE J 306		80W-90
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	898
Dynamic viscosity at -26°	DIN 51377	mPas	130,000
Kinematic viscosity at 40 °C	DIN 51398	mm <sup>2</sup> /s	139
Kinematic viscosity at 100 °C	DIN 51398	mm <sup>2</sup> /s	14.1
Flash point COC	DIN ISO 2592	°C	220
Pour point	DIN ISO 3016	°C	-27
FZG test A/8.3/90	DIN ISO 14635		>12

*All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.*