



PRODUCT INFORMATION

oilfino Sponte ATF A



DESCRIPTION

Transmission oil for automatic transmissions according to the GM specification ATF type A suffix A as well as power steering, fluid couplings and hydraulics in cars, trucks, buses and construction machinery.

PROPERTIES

A high degree of shifting comfort is achieved by matching the friction linings used in the transmission. Due to its excellent oxidation stability and precisely defined constant friction behaviour, oilfino ATFA offers very high wear protection in the transmission. Manufacturer's instructions must be observed due to various requirements for the coefficients of friction of the automatic oils.

RECOMMENDATION

- General Motors ATF Type A Suffix A (TASA)
- MB 236.2
- MAN 339 Type A
- Renk Doromat
- Allison C-3

Specific data	Method	Unit	oilfino Sponte ATF A
Colour			Red
Density at 15°C	DIN 51757	kg/m ³	866
Kinematic viscosity at 40 °C	D 445	mm ² /s	34.1
Kinematic viscosity at 100 °C	D 445	mm ² /s	7.3
Viscosity index	D 2270		182
Flash point	D 92	°C	208
Pour point	D 97	°C	-45

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.