



oilfino Sponte ATF II



DESCRIPTION

Transmission oil for automatic transmissions as well as power steering, fluid couplings and hydraulics in cars, trucks, buses and construction machinery.

PROPERTIES

A high degree of shifting comfort is achieved by matching the friction linings used in the transmission. oilfino Sponte ATF II meets the GM Dexron II D specification and is prescribed by well-known automotive manufacturers who use automatic transmissions with the Dexron II D requirement. Due to its excellent oxidation stability and precisely defined constant friction behaviour, oilfino Sponte ATF II offers very high wear protection in the transmission. Manufacturer's instructions must be observed due to various requirements for the coefficients of friction of the automatic oils.

RECOMMENDATION

- General Motors Dexron II D
- Ford Mercon
- MB Release 236.1
- MB Release DTFR 13C100
- Caterpillar TO-2
- Allison C-4
- MAN 339 Type L 2
- ZF Release Number ZF000438/ ZF TE-ML
- 04D/ 14A
- Voith H55.6335.XX (G 607)

RELEASES

- MB release 236.1
- ZF release number ZF000438/ ZF TE-ML 04D/ 14A
- MAN 339 type Z1
- MAN 339 type V1

Specific data	Method	Unit	oilfino Sponte ATF II
Colour			Red
Density at 15°C	DIN 51757	kg/m ³	871
Kinematic viscosity at 40 °C	DIN 51562	mm ² /s	36.1
Kinematic viscosity at 100 °C	DIN 51562	mm ² /s	7.2
Viscosity index	D 2270		168
Flash point	DIN ISO 2592	°C	210
Pour point	DIN ISO 3016	°C	-48

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.