



## PRODUCT INFORMATION

# oilfino Econ 4300 30W



## DESCRIPTION

**oilfino Econ 4300** is a universal high-performance single-range oil for use in diesel engines of agricultural equipment, construction machinery and commercial vehicles in compliance with manufacturer's regulations. It can also be used as hydraulic oil, in hydraulic clutches, manual transmissions, converter transmissions and retarders.

## PROPERTIES

oilfino Econ 4300 ensures wear protection through the selected combination of high-quality base oils and selected additives and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevent the formation of black sludge.

## SPECIFICATIONS

- API CF-4/CF/SF

## RECOMMENDATION

- MTU MTL 5044 Type 1
- MB 228.0
- MAN 270
- ZF TE-ML 04A
- Allison C-4
- Caterpillar TO-2
- Volvo VDS

Specific data	Method	Unit	oilfino Econ 4300 SAE 30
SAE grade	DIN 51511		30
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	891
Viscosity at 40 °C	DIN 51562	mm <sup>2</sup> /s	106
Viscosity at 100 °C	DIN 51562	mm <sup>2</sup> /s	11.7
Viscosity index	DIN ISO 2909		99
Flash point	DIN ISO 2592	°C	264
Pour point	DIN ISO 3016	°C	-24
Base number	DIN ISO 3771	mgKOH/g	11.6
Sulphate ash	DIN 51575	g/100g	1.6

*All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.*