



PRODUCT INFORMATION

oilfino Econ 4400 40W



DESCRIPTION

oilfino Econ 4400 is a universal high-performance single-range oil for use in diesel engines of agricultural equipment, construction machinery and commercial vehicles in compliance with manufacturer's regulations. It can also be used as hydraulic oil, in hydraulic clutches, manual transmissions, converter transmissions and retarders.

PROPERTIES

oilfino Econ 4400 ensures wear protection through the selected combination of high-quality base oils and selected additives, and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevent the formation of black sludge.

SPECIFICATIONS

- API CF-4/CF/SF

RECOMMENDATION

- MTU MTL 5044 Type 1
- MB 228.0
- MAN 270
- ZF TE-ML 04A
- Allison C-4
- Caterpillar TO-2
- Volvo VDS

| Specific data | Method | Unit | oilfino Econ 4400 SAE 40 |
|---------------------|--------------|--------------------|--------------------------|
| SAE grade | DIN 51511 | | 40 |
| Density at 15°C | DIN 51757 | kg/m ³ | 897 |
| Viscosity at 40 °C | DIN 51562 | mm ² /s | 166 |
| Viscosity at 100 °C | DIN 51562 | mm ² /s | 15.3 |
| Viscosity index | DIN ISO 2909 | | 95 |
| Flash point | DIN ISO 2592 | °C | 280 |
| Pour point | DIN ISO 3016 | °C | -24 |
| Base number | DIN ISO 3771 | mgKOH/g | 11.6 |
| Sulphate ash | DIN 51575 | g/100g | 1.6 |

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.