



PRODUCT INFORMATION

oilfino Econ 5000 15W-40



DESCRIPTION

oilfino Econ 5000 is a multi-range engine oil for diesel and petrol engines with or without turbocharging. It ensures reliable cold starts all year round and shear-stable active ingredients allow high-temperature resistance over the full oil residence time. oilfino Econ 5000 was developed for the universal supply of mixed fleets.

PROPERTIES

oilfino Econ 5000 ensures wear protection through the selected combination of high-quality base oils and selected additives, and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevent the formation of black sludge.

SPECIFICATIONS

- API SJ/CF-4

RECOMMENDATION

- MAN 271
- MTU MTL 5044 Typ 1
- MB 229.1
- Volvo VDS
- MB 228.1
- Allison C-4

Specific data	Method	Unit	oilfino Econ 5000 15W-40
SAE grade	DIN 51511		15W-40
Density at 15°C	DIN 51757	kg/m ³	882
Viscosity at 40 °C	DIN 51562	mm ² /s	105
Viscosity at 100 °C	DIN 51562	mm ² /s	14.0
Viscosity index	DIN ISO 2909		133
Flash point	DIN ISO 2592	°C	230
Pour point	DIN ISO 3016	°C	-33
Base number	DIN ISO 3771	mgKOH/g	8.9
Sulphate ash	DIN 51575	g/100g	1.1

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.