



PRODUCT INFORMATION

oilfino Econ T 8000 10W-40



DESCRIPTION

oilfino Econ T 8000 is a semi-synthetic Super High Performance Diesel (SHPD) engine oil for use in engines subject to high mechanical and thermal loads, with and without turbocharging. It reliably ensures cold starting at low outside temperatures and full lubrication safety at high operating temperatures. The use of selected additives ensures use during extended oil change intervals and reduces maintenance costs. oilfino Econ T 8000 has been designed for use in mixed fleets with diesel and petrol engines, in cars, lorries and construction machinery.

PROPERTIES

oilfino Econ T 8000 ensures wear protection through the selected combination of high-quality base oils and selected additives, and ensures excellent engine cleanliness. The optimal protection against bore polishing prevents excessive oil consumption and the excellent cleaning and sludge carrying capacity reliably prevents the formation of black sludge. The excellent oxidation and temperature stability ensures safe operation even under more severe conditions and enables extended oil change intervals according to manufacturer specifications.

SPECIFICATIONS

- ACEA E7
- ACEA E7/ A3/B4
- API CI-4

RECOMMENDATION

- Global DHD-1
- Volvo VDS-3 (STD 417-0002)
- MTU MTL 5044 Typ 2
- JASO DH-1
- Cummins CES 20076/ 20077/ 20078
- Allison C-4
- MB 228.3
- Renault VI RLD 2
- DEUTZ DQC-III 18
- MB 229.1
- DAF
- Voith Retarder Typ A
- MB 235.27
- Mack EO-N/ EO-M Plus
- Detroit Diesel DDC 93 K 215
- MAN M 3275-1

RELEASES

- Volvo VDS-3 (STD 417-0002)
- Renault VI RLD 2
- Mack EO-N
- MB 228.3

Specific data	Method	Unit	oilfino Econ T 8000 10W-40
SAE grade	DIN 51511		10W-40
Density at 15°C	DIN 51757	kg/m ³	871
Dynamic viscosity at -25°	DIN 51377	mPa.s	5.950
Viscosity at 40 °C	DIN 51562	mm ² /s	96.6
Viscosity at 100 °C	DIN 51562	mm ² /s	14.8
Viscosity index	DIN ISO 2909		158
Flash point	DIN ISO 2592	°C	229
Pour point	DIN ISO 3016	°C	-42
Base number	DIN ISO 3771	mgKOH/g	10.8

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.